Castleton TruHybrid™ wood Stove





FINISH OPTIONS:



Matte Black




Brown Majolica Enamel




Seafoam Enamel




CLEARANCE TO COMBUSTIBLE MATERIALS



	Single-wall connector pipe, no rear heat shield	Double-wall connector pipe*, with rear heat shield
Α	17"	17"
В	15"	8"
С	20"	13"
D	8"	8"
Е	20.5"	20.5"





Minimum Hearth Protection US/Canada: Ember Protection Only

Note: Clearance measurements refer to the top of the stove.

* Connector pipe clearances may vary. Refer to manufacturer's specifications.



This wood-burning appliance meets 2020 U.S. Environmental Protection Agency clean air standards.

CASTLETON 8031

TruHybrid[™]

- TruHybrid™ Combustion System Clean burning, uber-efficient, burn times up to 20 hours.
- Single Lever Air Control
 Easy operation, consistent performance
- Easy Catalyst Control Handle
 Open side lever for smokeless startups, close for long, efficient fires
- Durable Construction
 1¼" soapstone with iron protectors ensure a lifetime of trouble free service
- Top Or Rear Flue Exit
 Flexible installation, free standing or hearth configuration with a cooking plate

SPECIFICATIONS

Burn Time	20+ hrs
EPA Certified	0.69 g/hr
Heats up to	1,500 sq ft
Firebox Capacity	1.9 cu ft
BTU	Up to 45,000
Efficiency	83% LHV, 77% HHV
Maximum Log Length	18"
Flue Exit & Diameter	Top or Rear - 6″
Ash Pan	n/a
Actual Weight	464 lbs.
Alcove Certified	Yes
Mobile Home Certified	Yes

ACCESSORIES

Rear Heat Shield	90-68300
Convection Blower	90-57210
Outside Air Adapter	90-53300
Spark Screen	. 90-69300

Note: Always refer to the HearthStone Owner's Manual and the local Authority Having Jurisdiction in your area for the specific installation requirements for your product.